

# Batterieladegeräte 80 Volt



## Filon Classic Wa/ Wa-Puls DIN 41774

Batterie- spannung	Gerätetyp				Netzanschluss		Gehäuse		Abmessung	Gewicht
	Netz- spannung	Lade- spannung	Lade- strom	Bez.	Leistung	Sich. AT	Typ	Bez.	B x H x T	
	[V]	[V]	[A]		kVA	[A]			[mm]	
<b>80V</b>	E 230	80V	/ 15	B1-FML	1,5	8,0	KL-300	M	360x210x260	17
	E 230	80V	/ 20	B1-FML	2,0	16,0	KL-350	L	515x460x385	27
	E 230	80V	/ 25	B1-FML	2,5	16,0	KL-350	L	515x460x385	29
	D 400	80V	/ 30	B1-FML	3,0	3x8,0	KL-400	XL	515x700x385	50
	D 400	80V	/ 40	B1-FML	5,0	3x10,0	KL-400	XL	515x700x385	60
	D 400	80V	/ 50	B1-FML	6,0	3x10,0	KL-400	XL	515x700x385	70
	D 400	80V	/ 60	B1-FML	7,0	3x10,0	KL-400	XL	515x700x385	70
	D 400	80V	/ 70	B1-FML	8,0	3x16,0	KL-400	XL	515x700x385	80
	D 400	80V	/ 80	B1-FML	9,0	3x16,0	KL-400	XL	515x700x385	80
	D 400	80V	/ 90	B1-FML	10,0	3x16,0	KL-400	XL	515x700x385	90
	D 400	80V	/ 100	B1-FML	11,0	3x16,0	KL-400	XL	515x700x385	90
	D 400	80V	/ 110	B1-FML	11,5	3x16,0	KL-400	XL	515x700x385	95
	D 400	80V	/ 120	B1-FML	12,0	3x20,0	KL-500	XL	700x1000x500	100
	D 400	80V	/ 130	B1-FML	13,0	3x25,0	KL-500	XL	700x1000x500	110
	D 400	80V	/ 140	B1-FML	14,0	3x25,0	KL-500	XL	700x1000x500	140
	D 400	80V	/ 150	B1-FML	15,0	3x25,0	KL-500	XL	700x1000x500	150
	D 400	80V	/ 160	B1-FML	16,0	3x35,0	KL-500	XL	700x1000x500	160
	D 400	80V	/ 170	B1-FML	17,0	3x35,0	KL-500	XL	700x1000x500	170
	D 400	80V	/ 180	B1-FML	18,0	3x35,0	KL-500	XL	700x1000x500	180
	D 400	80V	/ 190	B1-FML	19,0	3x35,0	KL-500	XL	700x1000x500	200
	D 400	80V	/ 200	B1-FML	20,0	3x35,0	KL-500	XL	700x1000x500	200
	D 400	80V	/ 210	B1-FML	21,0	3x35,0	KL-500	XL	700x1000x500	210
	D 400	80V	/ 220	B1-FML	22,0	3x35,0	KL-500	XL	700x1000x500	220
	D 400	80V	/ 230	B1-FML	23,0	3x35,0	KL-500	XL	700x1000x500	230
	D 400	80V	/ 240	B1-FML	24,0	3x50,0	KL-500	XL	700x1000x500	240
D 400	80V	/ 250	B1-FML	25,0	3x50,0	KL-500	XL	700x1000x500	250	

Alle Geräte incl. Netzleitung mit Stecker .

Ladestecker gegen Aufpreis in jeder Ausführung Lieferbar

Elektrolytumwälzung gegen Aufpreis lieferbar