

Batterieladegeräte 36 Volt



Filon Classic WOWa DIN 41774

Batterie- spannung	Gerätetyp				Netzanschluss		Gehäuse		Abmessung	Gewicht
	Netz- spannung	Lade- spannung	Lade- strom	Bez.	Leistung	Sich. AT	Typ	Bez.	B x H x T	
	[V]	[V]	[A]		kVA	[A]			[mm]	
36V	E 230	36V	/ 15	B2-FML	0,9	4,0	KL-300	M	360x210x260	15
	E 230	36V	/ 20	B2-FML	1,2	6,3	KL-300	M	360x210x260	16
	E 230	36V	/ 25	B2-FML	1,5	6,3	KL-300	M	360x210x260	17
	E 230	36V	/ 30	B2-FML	1,8	8,0	KL-300	M	360x210x260	18
	E 230	36V	/ 40	B2-FML	2,2	8,0	KL-300	M	360x210x260	21
	E 230	36V	/ 50	B2-FML	2,6	16,0	KL-350	L	515x460x385	25
	E 230	36V	/ 60	B2-FML	3,0	16,0	KL-350	L	515x460x385	37
	E 230	36V	/ 70	B2-FML	4,0	16,0	KL-350	L	515x460x385	41
	D 400	36V	/ 80	B2-FML	4,5	3x10,0	KL-350	L	515x460x385	52
	D 400	36V	/ 90	B2-FML	4,8	3x10,0	KL-350	L	515x460x385	54
	D 400	36V	/ 100	B2-FML	6,0	3x10,0	KL-400	XL	515x700x385	65
	D 400	36V	/ 110	B2-FML	6,0	3x10,0	KL-400	XL	520x700x385	65
	D 400	36V	/ 120	B2-FML	6,0	3x10,0	KL-400	XL	520x700x385	66
	D 400	36V	/ 130	B2-FML	6,2	3x10,0	KL-400	XL	520x700x385	67
	D 400	36V	/ 140	B2-FML	6,5	3x10,0	KL-400	XL	520x700x385	68
	D 400	36V	/ 150	B2-FML	6,75	3x16,0	KL-400	XL	520x700x385	70
	D 400	36V	/ 160	B2-FML	7,2	3x16,0	KL-400	XL	520x700x385	75
	D 400	36V	/ 170	B2-FML	7,6	3x16,0	KL-400	XL	520x700x385	80
	D 400	36V	/ 180	B2-FML	8,0	3x16,0	KL-400	XL	520x700x385	85
	D 400	36V	/ 190	B2-FML	8,5	3x16,0	KL-400	XL	520x700x385	85
	D 400	36V	/ 200	B2-FML	9,0	3x16,0	KL-400	XL	520x700x385	90
	D 400	36V	/ 210	B2-FML	9,5	3x16,0	KL-400	XL	520x700x385	93
	D 400	36V	/ 220	B2-FML	10,0	3x20,0	KL-400	XL	520x700x385	95
	D 400	36V	/ 230	B2-FML	11,0	3x20,0	KL-400	XL	520x700x385	100
D 400	36V	/ 240	B2-FML	12,0	3x20,0	KL-400	XL	520x700x385	105	
D 400	36V	/ 250	B2-FML	13,0	3x20,0	KL-500	XL	700x1000x500	110	

Alle Geräte incl. Netzleitung mit Stecker .
 Ladestecker gegen Aufpreis in jeder Ausführung Lieferbar
 Elektrolytumwälzung gegen Aufpreis lieferbar