

Batterieladegeräte 48 Volt

Filon Classic W0Wa DIN 41774

Batterie- spannung	Gerätetyp				Netzanschluss		Gehäuse		Abmessung	Gewicht
	Netz- spannung	Lade- spannung	Lade- strom	Bez.	Leistung	Sich. AT	Typ	Bez.	B x H x T	
	[V]	[V]	[A]		kVA	[A]			[mm]	
48V	E 230	48V	/ 15	B2-FML	1,2	4,00	KL-300	M	360x210x260	22
	E 230	48V	/ 20	B2-FML	1,5	6,3	KL-300	M	360x210x260	25
	E 230	48V	/ 25	B2-FML	2,0	8,0	KL-300	M	360x210x260	27
	E 230	48V	/ 30	B2-FML	2,4	10,0	KL-300	M	360x210x260	29
	E 230	48V	/ 40	B2-FML	3,5	16,0	KL-350	L	515x460x385	42
	E 230	48V	/ 50	B2-FML	4,0	16,0	KL-350	L	515x460x385	45
	D 400	48V	/ 60	B2-FML	4,5	3x10,0	KL-400	XL	520x700x385	65
	D 400	48V	/ 70	B2-FML	4,8	3x10,0	KL-400	XL	520x700x385	70
	D 400	48V	/ 80	B2-FML	4,8	3x10,0	KL-400	XL	520x700x385	75
	D 400	48V	/ 90	B2-FML	5,0	3x16,0	KL-400	XL	520x700x385	82
	D 400	48V	/ 100	B2-FML	6,0	3x16,0	KL-400	XL	520x700x385	85
	D 400	48V	/ 110	B2-FML	6,5	3x16,0	KL-400	XL	520x700x385	87
	D 400	48V	/ 120	B2-FML	7,0	3x16,0	KL-400	XL	520x700x385	90
	D 400	48V	/ 130	B2-FML	8,0	3x16,0	KL-400	XL	520x700x385	92
	D 400	48V	/ 140	B2-FML	9,0	3x16,0	KL-400	XL	520x700x385	95
	D 400	48V	/ 150	B2-FML	9,0	3x16,0	KL-400	XL	520x700x385	98
	D 400	48V	/ 160	B2-FML	9,5	3x20,0	KL-400	XL	520x700x385	100
	D 400	48V	/ 170	B2-FML	10,0	3x20,0	KL-400	XL	520x700x385	102
	D 400	48V	/ 180	B2-FML	10,5	3x20,0	KL-400	XL	520x700x385	105
	D 400	48V	/ 190	B2-FML	11,0	3x25,0	KL-400	XL	520x700x385	110
D 400	48V	/ 200	B2-FML	12,0	3x25,0	KL-400	XL	520x700x385	110	
D 400	48V	/ 210	B2-FML	13,5	3x25,0	KL-500	XL	700x1000x500	115	
D 400	48V	/ 220	B2-FML	13,5	3x25,0	KL-500	XL	700x1000x500	115	
D 400	48V	/ 230	B2-FML	14,0	3x25,0	KL-500	XL	700x1000x500	118	
D 400	48V	/ 240	B2-FML	15,0	3x25,0	KL-500	XL	700x1000x500	120	
D 400	48V	/ 250	B2-FML	16,0	3x25,0	KL-500	XL	700x1000x500	125	

Alle Geräte incl. Netzleitung mit Stecker .
Ladestecker gegen Aufpreis in jeder Ausführung Lieferbar
Elektrolytumwälzung gegen Aufpreis lieferbar