

Batterieladegeräte 80 Volt

Filon Classic W0Wa DIN 41774

Batterie- spannung	Gerätetyp				Netzanschluss		Gehäuse		Abmessung	Gewicht
	Netz- spannung	Lade- spannung	Lade- strom	Bez.	Leistung	Sich. AT	Typ	Bez.	B x H x T	
	[V]	[V]	[A]		kVA	[A]			[mm]	
80V	E 230	80V	/ 15	B2-FML	1,5	8,00	KL-300	M	360x210x260	17
	E 230	80V	/ 20	B2-FML	2,0	16,0	KL-350	L	515x460x385	27
	E 230	80V	/ 25	B2-FML	2,5	16,0	KL-350	L	515x460x385	29
	D 400	80V	/ 30	B2-FML	3,0	3x8,0	KL-400	XL	520x700x385	50
	D 400	80V	/ 40	B2-FML	5,0	3x10,0	KL-400	XL	520x700x385	60
	D 400	80V	/ 50	B2-FML	6,0	3x10,0	KL-400	XL	520x700x385	70
	D 400	80V	/ 60	B2-FML	7,0	3x10,0	KL-400	XL	520x700x385	70
	D 400	80V	/ 70	B2-FML	8,0	3x16,0	KL-400	XL	520x700x385	80
	D 400	80V	/ 80	B2-FML	9,0	3x16,0	KL-400	XL	520x700x385	80
	D 400	80V	/ 90	B2-FML	10,0	3x16,0	KL-400	XL	520x700x385	90
	D 400	80V	/ 100	B2-FML	11,0	3x16,0	KL-400	XL	520x700x385	90
	D 400	80V	/ 110	B2-FML	11,5	3x16,0	KL-400	XL	520x700x385	95
	D 400	80V	/ 120	B2-FML	12,0	3x20,0	KL-500	XL	700x1000x500	100
	D 400	80V	/ 130	B2-FML	13,0	3x25,0	KL-500	XL	700x1000x500	110
	D 400	80V	/ 140	B2-FML	14,0	3x25,0	KL-500	XL	700x1000x500	140
	D 400	80V	/ 150	B2-FML	15,0	3x25,0	KL-500	XL	700x1000x500	150
	D 400	80V	/ 160	B2-FML	16,0	3x35,0	KL-500	XL	700x1000x500	160
	D 400	80V	/ 170	B2-FML	17,0	3x35,0	KL-500	XL	700x1000x500	170
	D 400	80V	/ 180	B2-FML	18,0	3x35,0	KL-500	XL	700x1000x500	180
	D 400	80V	/ 190	B2-FML	19,0	3x35,0	KL-500	XL	700x1000x500	200
D 400	80V	/ 200	B2-FML	20,0	3x35,0	KL-500	XL	700x1000x500	200	
D 400	80V	/ 210	B2-FML	21,0	3x35,0	KL-500	XL	700x1000x500	210	
D 400	80V	/ 220	B2-FML	22,0	3x35,0	KL-500	XL	700x1000x500	220	
D 400	80V	/ 230	B2-FML	23,0	3x35,0	KL-500	XL	700x1000x500	230	
D 400	80V	/ 240	B2-FML	24,0	3x50,0	KL-500	XL	700x1000x500	240	
D 400	80V	/ 250	B2-FML	25,0	3x50,0	KL-500	XL	700x1000x500	250	

Alle Geräte incl. Netzleitung mit Stecker .
Ladestecker gegen Aufpreis in jeder Ausführung lieferbar
Elektrolytumwälzung gegen Aufpreis lieferbar